

SpecFun

A Special Functions Library

for the HP48 with ALG48

Version 4.2

Mika Heiskanen

Claude-Nicolas Fiechter

© 1994-98

1 Acknowledgements, copyright & disclaimer of warranty

All the files of the **SpecFun** and **ALG48** libraries are copyrighted © by Claude-Nicolas Fiechter and Mika Heiskanen.

SpecFun is distributed in the hope that it will be useful, but the copyright holders provide the program “as is” without warranty of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchandability and fitness for a particular purpose. In no event will the copyright holders be liable to you for damages, including any general, special, incidental or consequential damages arising out of the use or inability to use the program.

This version of **SpecFun** is a GiftWare release. You may use it as long as you like, but only for non-commercial purposes and only as a private person. Permission to copy the whole, unmodified, **SpecFun** library is granted provided that the copies are not made or distributed for resale (excepting nominal copying fees) and provided that you conspicuously and appropriately include on each copy this copyright notice and disclaimer of warranty.

Special thanks to Dr. Mark A. Ordal whose Bessel function implementations were the basis for the ones in **SpecFun**.

2 Overview

SpecFun defines a number of commonly used “special functions” not provided by the **HP48**, including Bessel functions, error functions, Gamma and Beta functions, and polynomial generating functions. Polynomial generating functions include Legendre, Hermite, Tschebyscheff and Laguerre polynomials as well as spherical harmonics.

SpecFun works in conjunction with the **ALG48** library © by Claude-Nicolas Fiechter and Mika Heiskanen and needs **ALG48** to be installed to work properly (see the warning below). The function names in **SpecFun** were chosen so as to be displayed in the customary way when using the **EQSTK** library © by the same authors.

3 Installation

SpecFun takes approximately 6Kb of memory and works in both **HP48GX** and **HP48SX**. **SpecFun** uses some of the internal subroutines in **ALG48**, and thus requires it to be installed. See the **ALG48** documentation for information on installing **ALG48**.

Warning: Only use this library with the version of **ALG48** with which it was distributed. Do not use it with an older version of **ALG48** or with the **RSIM** library. If you do it will probably crash your calculator.

Due to the special optimization features used in **ALG48**, not all storage combinations are allowed. The following ones are possible:

- In **SX** there are no restrictions
- In **GX** if **ALG48** is in port 0 or port 1 then **SpecFun** can be stored in any port.
- In **GX** if **ALG48** is stored in port 2 (or higher) then **SpecFun** must be stored in the same port, or port 0.

Installing **ALG48** and **SpecFun** in the same port seems the most natural choice and is recommended.

SpecFun is an auto-attaching library (library number 911). To install it on your **HP48** download the file **specfun.lib** onto your calculator (in *binary* mode), put the content of the created variable on the stack, store it the port of your choice (e.g., '**SPECFUN.LIB**' **DUP RCL SWAP PURGE 0 STO**) and power-cycle the calculator.

4 Commands

The functions defined by **SpecFun** are divided in two groups: special functions and polynomial generating functions. We give below the definitions of all the functions implemented in **SpecFun**. Section 4.3 gives some example of utilization.

4.1 Special Functions

The special functions accept all combinations of real and symbolic arguments, but are evaluated only for real arguments. To evaluate the Bessel functions the order argument n has to be an integer value, otherwise an **"Undefined Result"** error is generated.

- Gamma Function

$$\mathbf{GAMMA}(x) = \int_0^{\infty} e^{-t} t^{x-1} dt \quad , \quad x > 0$$

- Beta Function

$$\mathbf{BETA}(x, y) = \int_0^1 t^{x-1} (1-t)^{y-1} dt = \frac{\mathbf{GAMMA}(x)\mathbf{GAMMA}(y)}{\mathbf{GAMMA}(x+y)} \quad , \quad x, y > 0$$

- Error Functions

$$\begin{aligned} \mathbf{ERF}(x) &= \frac{2}{\pi} \int_0^x e^{-t^2} dt \\ \mathbf{ERFC}(x) &= \frac{2}{\pi} \int_x^{\infty} e^{-t^2} dt = 1 - \mathbf{ERF}(x) \end{aligned}$$

- Bessel Functions

$$\begin{aligned} \mathbf{J.n}(n, x) &= J_n(x) = \sum_{r=0}^{\infty} \frac{(-1)^r (x/2)^{n+2r}}{r! \cdot \mathbf{GAMMA}(n+r+1)} \\ \mathbf{Y.n}(n, x) &= Y_n(x) = \lim_{p \rightarrow n} \frac{J_p(x) \cos(p\pi) - J_{-p}(x)}{\sin(p\pi)} \quad , \quad x \geq 0 \\ \mathbf{I.n}(n, x) &= I_n(x) = i^{-n} J_n(ix) \\ \mathbf{K.n}(n, x) &= K_n(x) = \lim_{p \rightarrow n} \frac{I_{-p}(x) - I_p(x)}{\sin(p\pi)} \cdot \frac{\pi}{2} \quad , \quad x \geq 0 \end{aligned}$$

- Quick access commands

$$\begin{aligned} \mathbf{J.0}(x) &= J_0(x) \\ \mathbf{J.1}(x) &= J_1(x) \end{aligned}$$

4.2 Polynomial Generating Functions

The polynomial generating functions expect the order arguments (n, m) to be positive integer values and the variables (x, a, b) to be symbolic or identifier objects. A simplified output form is used for the Legendre polynomials when the variable argument is of the form “ $\cos(x)$ ”, for some arbitrary sub-expression x (see Section 4.3).

- Legendre Polynomials

$$\begin{aligned} \mathbf{P.n}(n, x) &= P_n(x) = \frac{1}{2^n n!} \cdot \frac{d^n}{dx^n} (x^2 - 1)^n \\ \mathbf{P.nm}(n, m, x) &= P_n^m(x) = (1 - x^2)^{m/2} \cdot \frac{d^m}{dx^m} P_n(x) \end{aligned}$$

- Spherical Harmonics

$$\mathbf{Y.nm}(n, m, a, b) = Y_n^m(a, b) = (-1)^m \sqrt{\frac{(2n+1)(n-m)!}{4\pi(n+m)!}} P_n^m(\cos a) e^{imb}$$

- Hermite Polynomials

$$\mathbf{H.n}(n, x) = H_n(x) = (-1)^n \cdot e^{x^2/2} \cdot \frac{d^n}{dx^n} e^{-x^2/2}$$

- Tschebyscheff Polynomials

$$\begin{aligned} \mathbf{T.n}(n, x) &= T_n(x) = \cos(n \cdot \arccos(x)) \\ \mathbf{U.n}(n, x) &= U_n(x) = \frac{\sin((n+1) \arccos(x))}{\sqrt{1-x^2}} \end{aligned}$$

- Laguerre Polynomials

$$\begin{aligned} \mathbf{L.n}(x) &= L_n(x) = \frac{e^x}{n!} \cdot \frac{d^n}{dx^n} (x^n e^{-x}) \\ \mathbf{L.nm}(x) &= L_n^m(x) = (-1)^m \frac{d^m}{dx^m} L_{n+m}(x) \end{aligned}$$

4.3 Examples

$5 \text{ X } \mathbf{P.n} \Rightarrow$	$\frac{1}{8}(63X^5 - 70X^3 + 15X)$	Standard output form
$2 \text{ 1 X } \mathbf{P.nm} \Rightarrow$	$3X(1 - X^2)^{1/2}$	Standard output form
$2 \text{ 1 COS(X) } \mathbf{P.nm} \Rightarrow$	$3 \cos(X) \sin(X)$	Special output for “ $\cos(x)$ ”
$2 \text{ 1 t p } \mathbf{Y.nm} \Rightarrow$	$-\sqrt{\frac{5}{24\pi}} \cdot 3 \cos(t) \sin(t) e^{ip}$	Usually $t, p = \theta, \phi$
$5 \text{ COS(X) } \mathbf{T.n} \Rightarrow$	$16 \cos(x)^5 - 20 \cos(x)^3 + 5 \cos(x)$	Expansion of $\cos(5x)$

5 Contact

Gifts :-), bug reports, and constructive comments and suggestions can be sent to either one of the following addresses.

Mika Heiskanen
Jämeräntaival 7 C 355
02150 ESPOO
Finland
`mheiskan@cc.hut.fi`

Claude-Nicolas Fiechter
Department of Computer Science
University of Pittsburgh
Pittsburgh, PA 15260, U.S.A.
`fiechter@cs.pitt.edu`