

## TruHPoint 1.0

I. Introduction. TruHPoint provides accurate pointing angles from earth stations to satellites. It is based on Intelsat Earth Station Standard (IESS) 412, which can be downloaded at [http://www.intelsat.com/satellites/satellites\\_technicalresources.asp](http://www.intelsat.com/satellites/satellites_technicalresources.asp). The purpose is to provide pointing angles with 3 decimal point accuracy for calibration of antenna control units. It also provides the times of ascension or declension of the satellite over the equator. For initially finding and peaking up on the satellite, it is much better to use SATIt, which can also be found at [www.hpcalc.org](http://www.hpcalc.org). SATIt provides pointing angles with 1 decimal point accuracy, and requires much less input data.

### II. Installation.

Select the TruHPoint file to transfer from the appropriate folder. Use binary transfer for speed and accuracy. TruHPoint should take about 7 k of memory, but you should have at least 2-3 k more available to accommodate report storage.

TruHPoint requires a text editor/viewer for viewing reports. The libraries can be found at [www.hpcalc.org](http://www.hpcalc.org). Please follow installation instructions included with the libraries.

HP48 -- TED  
HP49 -- Lupa

### III. Operation:

#### 1. Preliminaries.

a. Download the most recent 11 parameter ephemeris data from the satellite provider. A sample report is shown in Appendix A. Intelsat data can be obtained at the link indicated above. Other satellite suppliers normally have the data available on their web site.

b. To get the most out of TruHPoint, the calculator clock should be accurately set to Greenwich Mean Time.

#### 2. Basic operation.

a. The [VAR] soft key menu should be as follows:

Soft Key Description

-----data input -----

EPOC Opens an INFORM dialog to enter epoch and report parameters. The epoch year, month, etc. are on the 11 parameter report. The last two items pertain to the report(s) to be generated. MBC is minutes between calculations. This should be between 10 and 90. A smaller

number means more calculations and a longer report. A larger number means faster execution but slightly less accuracy. DUR is the duration in days for the report.

PARM Opens an INFORM dialog for entering the 11 ephemeris parameters.

ESTA Opens an INFORM dialog for the earth station. The ID or name of the earth station, latitude (negative for south), east longitude, and elevation in km are required.

-----report generation -----

AZNW AZimuth and elevation NoW. Provides a report of current pointing angles (you did set the calculator clock to GMT, didn't you?). Pressing [ON] after the report is in view will leave the azimuth on stack level 2 and elevation on stack level 1 for easy reference while calibrating the antenna controller. Note that this is the observed elevation angle that compensates for atmospheric refraction rather than the geometric elevation angle.

AZTB AZimuth and elevation TaBle. (see Appendix B for a sample). This is the shorter of the two tabular reports. The report is a columnar list of azimuth and observed elevation angles by date and time. An "A" or "D" after a line indicates that the satellite has ascended (south to north) or descended (north to south) the equator since the last time calculated. These are the best times to peak up a manual or jog track system.

LGTB LonG TaBle Same as AZTB but includes actual satellite position on each line.

EXIT Erases the report from memory and leaves the TruHPoint program. If you want to keep the report for later viewing, just leave with UPDIR or HOME keys

-----

Important notes:

1. These reports contain many calculations that will take several minutes. Please be patient. If you are in a hurry, try to cut out the header (see below), increase the minutes between calculations, or decrease the number of days for the reports.
2. The header on any of the reports includes a calculated +170 hour satellite position. This should match the 170 hour prediction included in the 11 parameter report (Appendix A). This is a good check to make sure that the ephemeris were entered correctly.

a. The [CST] soft key menu operates as follows:

Soft Key Description

VIEW VIEW the current report

PRDEV (HP48 only) Selects IR or wire for PRinting DEVice.

PRINT PRINT the current report

RSTF ReSTores Flags to original condition. This is normally accomplished through program action. But, if you cancel a report in progress by pressing [ON], the original flags can be restored with this soft key.

HDR HeaDeR toggle. Press to select whether or not the header is included in each report. You probably will want the header the first time to double check the input data and +170 hour satellite location calculation.

RECL RECaLl.. Puts the last calculated Azimuth on level 2 and Elevation on level 1.

EXIT Same as VAR menu

V. Revision history:

Initial Release. 27 March 2002.

VI. Disclaimer. Copyright 2002 by Mike Richards. The software is provided free of charge, "as is," without any guarantee of any type, written or implied. You may distribute or use it in freeware only. You may not use it in any commercial product.

VII. References:

Intelsat Corporation. Intelsat Earth Station Standard (IESS) 412. 9 March 1990.

VIII. Please send comments or bug reports to:

Mike Richards  
[richam@mac.com](mailto:richam@mac.com)

Appendix A  
Sample Ephemeris Data Download

ROUTINE

FROM: INTELSAT WASHINGTON DC

TO: ALL STATIONS OPERATING AT 332.50 DEG EAST

SUBJECT: ELEVEN PARAMETER EPHEMERIS FOR INTELSAT 605/332.50  
DEG E

EARTH STATIONS PLEASE ON-PASS TO YOUR ADMINISTRATION

WEEKLY 11-PARAMETER DATA 20020323

THE 11 PARAMETER EPHEMERIS AND EPOCH PREDICTING THE SPACECRAFT  
MOTION ARE PROVIDED BELOW.

PLEASE ENTER THIS DATA INTO THE EPHEM.DAT FILE

YEAR	MONTH	DAY	HOUR	MINUTE	SECOND
2002	03	23	00	00	00

THE EPHEMERIS VALUES ARE:

LM0	LM1	LM2
DEG. E	DEG/DAY	DEG/DAY/DAY
332.5252	.0057	-.000749 (MINUS)

LONC	LONC1	LONS	LONS1
DEG. E	DEG/DAY	DEG. E	DEG/DAY
.0022	.0013	-.0116 (MINUS)	.0005

LATC	LATC1	LATS	LATS1
DEG. N	DEG/DAY	DEG. N	DEG/DAY
.0018	.0004	.0268	.0017

THE NOMINAL ORBITAL LOCATION FOR THIS SATELLITE IS 332.50 DEG. E

THE PREDICTED SATELLITE LONGITUDE AND LATITUDE AT 170 HOURS AFTER  
EPOCH ARE 332.5322 DEG. E. AND .0271 DEG. N.

BEST REGARDS  
MANAGER IOC

Appendix B  
Sample TruHPoint Report

E/S ID: Lima  
Lat(south): 12.0999°  
Long(East): 283.0834°  
Elevation: .125 km  
Interval: 60 min  
Duration: 4 days  
Epo: 02/23/02 00:00:00

Ephemeris:

LM0: 332.5060000  
LM1: 0.0063000  
LM2: -0.0007710  
LONC: 0.0027000  
LONC1: 0.0010000  
LONS: -0.0152000  
LONS1: 0.0008000  
LATC: 0.0088000  
LATC1: -0.0009000  
LATS: 0.0344000  
LATS1: 0.0026000

Calculated +170 hours:

332.514(E) .0337(N)

TIME AZIMUTH EL(obs)

DATE 02/23/02

00:00:00	79.828	32.160
01:00:00	79.816	32.162
02:00:00	79.805	32.163
03:00:00	79.797	32.165
04:00:00	79.791	32.166
05:00:00	79.789	32.167
06:00:00	79.789	32.168
07:00:00	79.794	32.169
08:00:00	79.801	32.169
09:00:00	79.811	32.169
10:00:00	79.822	32.169
11:00:00	79.835	32.168
12:00:00	79.849	32.166D
13:00:00	79.861	32.164
14:00:00	79.872	32.163
15:00:00	79.881	32.161
16:00:00	79.887	32.159
17:00:00	79.890	32.157
18:00:00	79.890	32.155
19:00:00	79.886	32.154
20:00:00	79.879	32.153
21:00:00	79.869	32.153
22:00:00	79.857	32.153
23:00:00	79.844	32.153

DATE 02/24/02

00:00:00	79.830	32.154A
01:00:00	79.818	32.155
02:00:00	79.806	32.156
03:00:00	79.797	32.158
04:00:00	79.791	32.159
05:00:00	79.788	32.160

. . .